

Bon[®]

SAFETY DATA SHEET

#32-121 - Liquiform™ Liquid Concrete Release Agent

Revision Date: March 19, 2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Liquiform™ Concrete Release Agent

Other Means of Identification: #32-121

Recommended Use: Liquid stamp release for concrete

Restrictions on Use: No Data

Supplier of the Safety Data Sheet Including Address:

Bon Tool
DBA Bonway
4430 Gibsonia Rd.
Gibsonia, PA 15044

Telephone Numbers

Company Phone Number Phone: 800-444-7060; 724-443-7080
Fax: 800-444-7065

Emergency Telephone - 24 Hr. Chem-Tel: 800-255-3924

2. HAZARD IDENTIFICATION

Category 3 Flammable Liquid

Category 1 Aspiration Hazard



Signal Word:

Danger

Hazard Statements:

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking

P233 Keep container tightly closed

P260 Do not breathe mist/vapors/spray

P264 Wash skin thoroughly after handling

P271 Use only outdoors or in a well-ventilated area

P281 Use personal protective equipment as required

Response:

P301+P310+P331 IF SWALLOWED: Do NOT induce vomiting. Immediately call a poison center or doctor/physician
P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340+P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician.

P305+p351+p338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash before reuse

P370+P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction

Storage:

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local/federal regulations.

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

	CAS #	OSHA PEL(TWA)	ACGIH(TLV-TWA)	Wt.%
C9-C11 Isoalkanes	68551-16-6	500 ppm	Not available	0.0 – 100.0

SECTION 4 FIRST AID MEASURES**Emergency First Aid Procedures**

Skin: Clean material from skin with soap and water followed by moisturizer.

Eyes: Flush with a gentle but large stream of clean water for 15 minutes, lifting the lower and upper eyelids occasionally. Call a physician if irritation persists.

Inhalation: Move to fresh air and provide oxygen if breathing is difficult. Seek medical attention if irritation persists.

Ingestion: DO NOT INDUCE VOMITING. Give large quantities of water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

SECTION 5 FIREFIGHTING PROCEDURES

Extinguishing Media: Dry chemical, CO₂, foam, water fog.

Flash Point (TCC): 118.4° F

Flammable Limits (% volume in air for solvents): LEL= No data available UEL= No data available

Special Fire Fighting Procedures: Evacuate area and fight fire from a distance. Firefighters wear NIOSH approved self-contained breathing apparatus. Cool containers exposed to fire with water. Vapors are heavier than air and may travel along the ground to distant ignition sources.

SECTION 6 SPILL OR LEAK PROCEDURES

Steps to Take if Material is Released or Spilled: No health effects expected from the clean-up of the material if contact can be avoided. Follow the protection information found in Section 8 of this SDS. Absorb spillage in suitable inert material. Sweep or scrape up and containerize.

SECTION 7 HANDLING AND STORAGE

Normal Handling: Always use good industrial hygiene practices and safety guidelines.

Storage: Store material in its original container. Keep containers tightly closed when not in use. Keep material away from open flame, sparks, or other sources of heat and ignition.

Waste Disposal Method: Dispose of material in accordance with federal, state, and local guidelines.

Special Precautions: Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld near the containers.

SECTION 8 PROTECTION INFORMATION

Respiratory Protection: Use NIOSH-approved organic vapor respirator when exposure levels cannot be maintained below limits or the chance of mist inhalation is present.

Ventilation: Provide adequate mechanical ventilation to keep exposure levels below TLV's.

Protective Gloves: Wear impervious chemical gloves.

Eye Protection: Wear chemical safety glasses.

Other Protective Clothing or Equipment: As needed to prevent repeated/prolonged contact.

Work/Hygienic Practices: Use only in adequately-ventilated area unless recommended respiratory protection is used. Wash thoroughly with soap and water after handling and before eating, smoking, or using washroom. If clothes become contaminated, change to clean clothing and wash contaminated clothes before re-use.

SECTION 9 PHYSICAL DATA

Appearance: Clear liquid

Odor: Typical hydrocarbon

Odor Threshold: No data available

pH: None

Freezing/Melting Point: No data available

Boiling Point: >381° F

Flash Point: 118.4° F

Evaporation Rate: <1 (n-butyl acetate=1)

Flammability (solid, gas): No data available

Upper/lower Flammability: No data available

Vapor Pressure: 0.1 mm Hg @ 20°C

Vapor Density (Air=1): >1

Relative Density: 0.8 g/cc

Solubility: Negligible solubility in water

Partition Coefficient: Not determined

Auto-ignition Temperature: >637°F

Decomposition temperature: Not determined

Viscosity: Not determined

Specific Gravity (H2O=1): 0.8

SECTION 10 REACTIVITY DATA

Reactivity: Stable.

Conditions to avoid: Prevent vapor accumulation. Avoid heat, sparks, and flames.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

Hazardous Polymerization: Should not occur.

Incompatibility (Materials to Avoid): Strong acids and oxidizing materials.

SECTION 11 TOXICITY DATA

Routes of Exposure: Inhalation, ingestion, eyes, and skin.

Acute Toxicity Lethal Doses (ATE):

LC50 (inhl) Not available

LD50 (oral) Not available

LD50 (skin) Not available

Health Hazards:

Acute: Minimally toxic. May cause eye, skin, gastrointestinal, and lung irritation. May cause central nervous system excitation followed by depression.

Chronic: Prolonged or repeated exposure can cause defatting and drying of the skin.

Skin Contact: May cause irritation and redness. Prolonged or repeated exposure can cause defatting and drying of the skin, which may result in a burning sensation and a dried, cracked appearance.

Eye Contact: May cause redness, tearing, blurred vision, and irritation of the eyes.

Inhalation: Overexposure may cause headache, nausea, dizziness, and loss of coordination.

Ingestion: May be harmful if swallowed. Aspiration of the material into the lungs can cause chemical pneumonitis, which can be fatal.

Carcinogen: None

Aggravation of Pre-existing Conditions: Persons with pre-existing skin, eye, or lung disorders may be more susceptible to the effects of the substance.

SECTION 12 ECOLOGICAL DATA

Acute Toxicity to Fish: No data available

Acute Toxicity to Aquatic Invertebrates: No data available

Toxicity to Aquatic Plants: No data available

Toxicity to Microorganisms: No data available

Chronic Toxicity to Fish: No data available

Chronic Toxicity to Aquatic Invertebrates: No data available

Persistence and Degradability: No data available

Bioaccumulation Potential: No data available

Mobility in the Soil: No data available

Other Adverse Effects: None established

SECTION 13 DISPOSAL INFORMATION

Waste Disposal Method: Liquid material carries RCRA waste code (D018). Dispose of material in accordance with all Federal, State, and Local regulations.

SECTION 14 TRANSPORT INFORMATION

For Domestic (US) Ground Transport: Non-Regulated Material in <119-gallon containers

For all other modes:

Proper Shipping Name: Non-Regulated Material

Hazard Class:

Packing Group:

Marine Pollutant:

SECTION 15 REGULATORY INFORMATION

SARA 311/312: Yes. (Acute, Chronic)

OSHA: This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200).

TSCA: Components of this material are either listed or are exempt from the EPA TSCA Inventory of Chemical Substances.

California Proposition 65: WARNING! This product contains <0.1% of a chemical known to the State of California to cause cancer.

Naphthalene

Ethylbenzene CAS#100-41-4 (<0.001%)

Benzene CAS#71-43-2 (<0.0001%)

WARNING! This product contains <1.0% of a chemical known to the State of California to cause reproductive harm.

Toluene CAS#108-88-3 (<0.0001%)

Benzene CAS#71-43-2 (<0.0001%)

Massachusetts Right To Know: None

Pennsylvania Right To Know: C9-C11 Isoalkanes 68551-16-6 0.0 – 100.0%
Hydrotreated light

New Jersey Right To Know: C9-C11 Isoalkanes 68551-16-6 0.0 – 100.0%

SECTION 16 ADDITIONAL INFORMATION

The regulatory information provided is not intended to be comprehensive. Federal, State and Local regulations may apply to this material.

DISCLAIMER: Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, manufacturer makes no representations as to the completeness or accuracy thereof.

BonTool Co.

® 4430 Gibsonia Rd., Gibsonia, PA 15044 • USA • (724) 443-7080 • FAX:(724) 443-7090
Emergency Phone: Chem-Tel 800-255-3924 (24 hours)

SD32121 4/7/2023
PAGE 4 of 4