

Bon[®]

SAFETY DATA SHEET

Solid Color Sealer

#42-370, 42-371, 42-372, 42-373, 42-374,
42-375, 42-376, 42-377, 42-378, 42-379, 42-380

Revision Date: May 12, 2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Exposed Solid Color Sealer

Other Means of Identification: 42-370, 42-371, 42-372, 42-373, 42-374, 42-375, 42-376, 42-377, 42-378,
42-379, 42-380

Recommended Use: Coloring and sealing decorative concrete.

Restrictions on Use: No Data

Supplier of the Safety Data Sheet Including Address:

Bon Tool
DBA Bonway
4430 Gibsonia Rd.
Gibsonia, PA 15044

Telephone Numbers

Company Phone Number

Phone: 800-444-7060; 724-443-7080

Fax: 800-444-7065

Emergency Telephone - 24 Hr/Chem-Tel: 800-255-3924

2. HAZARD IDENTIFICATION

Category 3 Flammable Liquid

Category 5 Acute Dermal Toxicity

Category 2 Carcinogen

Category 2A Eye Irritation

Category 2 Skin Irritation

Category 1 Skin Sensitization

Category 1B Reproductive Toxicity

Category 3 Specific Target Organ Acute Toxicity (respiratory system)

Category 2 Acute Aquatic Toxicity

Signal Word:

Danger



Hazard Statements:

H226 Flammable liquid and vapor
 H313 May be harmful in contact with skin
 H315 Causes skin irritation
 H317 May cause an allergic skin reaction
 H319 Causes serious eye irritation
 H335 May cause respiratory irritation
 H351 Suspected of causing cancer
 H360 May damage fertility or the unborn child
 H401 Toxic to aquatic life

Precautionary Statements:**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking
 P233 Keep container tightly closed
 P260 Do not breathe mist/vapors/spray
 P264 Wash skin thoroughly after handling
 P271 Use only outdoors or in a well-ventilated area
 P281 Use personal protective equipment as required

Response:

P301+P312+P331 IF SWALLOWED: Do NOT induce vomiting. Immediately call a poison center or doctor/physician if you feel unwell.
 P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
 P305+p351+p338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs, get medical advice/attention
 P370+P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction

Storage:

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local/federal regulations.

3. COMPOSITION/ INFORMATION ON INGREDIENTS**Hazardous components**

	<u>CAS #</u>	<u>OSHA PEL(TWA)</u>	<u>ACGIH(TLV-TWA)</u>	<u>Conc.(wt. %)</u>
Acrylic Polymer	Proprietary	Not established	Not established	14.0 – 20.0
p-Chlorobenzotrifluoride	98-56-6	Not established	Not established	50.0 – 60.0
bis(2-Ethylhexyl) phthalate	117-81-7	5 ppm	5 ppm	0.2 – 0.4
Solvent Naphtha, Heavy	Proprietary	17 ppm	5 mg/m3	10.0 – 11.1
1,2,4-Trimethylbenzene	95-63-6	25 ppm(1989 std.)	25 ppm	0.0 – 0.6
1,3,5-Trimethylbenzene	108-67-8	25 ppm	25 ppm	0.0 – 0.1
Naphthalene	91-20-3	10 ppm	10 ppm	0.0 – 0.6
Mixed xylene isomers	1330-20-7	100 ppm	100 ppm	0.0 – 0.8
Toluene	108-88-3	200 ppm	50 ppm	0.0 – 0.2

4. FIRST AID MEASURES

Emergency First Aid Procedures

Skin: Clean material from skin with acetone, then wash with soap and water followed by moisturizer. If irritation persists, contact a physician.

Eyes: Flush with a gentle but large stream of clean water for 15 minutes, lifting the lower and upper eyelids occasionally. Remove contact lenses if able. Call a physician if irritation persists.

Inhalation: Move to fresh air and provide oxygen if breathing is difficult. Seek medical attention.

Ingestion: DO NOT INDUCE VOMITING. Give large quantities of water. Do not give milk or alcoholic beverages. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

5. FIREFIGHTING PROCEDURES

Suitable Extinguishing Media: Dry chemical, CO₂, alcohol-resistant foam

Unsuitable Extinguishing Media: High-volume water jet

Flash Point (TCC): 109° F

Flammable Limits (% volume in air for solvents): LEL=0.9 UEL=10.5

Special Fire Fighting Procedures: Evacuate area and fight fire from a distance. Firefighters wear NIOSH approved self-contained breathing apparatus. Cool containers exposed to fire with water. Vapors are heavier than air and may travel along the ground to distant ignition sources. Do not allow runoff from firefighting to enter drains or water courses.

6. SPILL OR LEAK PROCEDURES

Steps to Take if Material is Released or Spilled: No health affects expected from the clean-up of the material if contact can be avoided. Follow the protection information found in Section 8 of this SDS. Ventilate the contaminated area. Prevent the spread of spilled material by using a suitable absorbent material or sand dam.

7. HANDLING AND STORAGE

Normal Handling: Always use good industrial hygiene practices and safety guidelines.

Storage: Store material in its original container. Keep containers tightly closed when not in use. Keep material away from open flame, sparks, or other sources of heat and ignition.

Waste Disposal Method: Liquid material is an ignitable waste (D001). Dispose of material in accordance with federal, state, and local guidelines.

Special Precautions: Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld on or near the containers.

8. Protection Information

Respiratory Protection: Use NIOSH-approved organic vapor respirator when exposure levels can't be kept below limits.

Ventilation: Provide adequate mechanical ventilation to keep exposure levels below TLV's.

Protective Gloves: Wear impervious chemical gloves.

Eye Protection: Wear chemical safety glasses.

Other Protective Clothing or Equipment: As needed to prevent repeated/prolonged contact.

Work/Hygienic Practices: Use only in adequately-ventilated area unless recommended respiratory protection is used. Wash thoroughly with soap and water after handling and before eating, smoking, or using washroom. If clothes become contaminated, change to clean clothing and wash contaminated clothes before re-use.

9. PHYSICAL DATA

Appearance: Opaque colored liquid
Odor: Naphthalenic
Odor Threshold: No data available
pH: None
Freezing/Melting Point: -36° F
Boiling Point: >282° F
Flash Point: 109° F
Evaporation Rate: 0.9 (butyl acetate = 1)
Flammability (solid, gas): No data available
Lower/Upper Flammability: 0.9 – 10.5
Vapor Pressure: 5.3 mm Hg at 20° C
Vapor Density: 6.2 (air=1)
Density: 1.36 g/cc
Solubility: Negligible
Partition Coefficient: No data available
Auto-ignition Temperature: No data available
Decomposition temperature: No data available
Viscosity: 20 - 30 centipoise

10. REACTIVITY DATA

Reactivity: Stable
Conditions to avoid: Prevent vapor accumulation. Avoid heat and flames.
Incompatibility (Materials to Avoid): Strong oxidizers, acids, alkalies, nitrates..
Hazardous Decomposition (Byproducts): Carbon monoxide, carbon dioxide, isobutylene, and acetic acid..
Hazardous Polymerization: Should not occur.

11. TOXICITY DATA

Routes of Exposure: Inhalation, Ingestion, eyes, and skin.

Acute Toxicity Lethal Doses (ATE):

LD50 (oral) 7189 mg/kg
LD50 (skin) 390
LC50 (inhl) 276.3 mg/l0 mg/kg

Health Hazards:

Acute: May cause eye, skin, gastrointestinal, and lung irritation.
Chronic: Prolonged and repeated exposures to high concentrations may cause respiratory damage.
Skin Contact: May cause irritation and redness. Prolonged or repeated exposure can cause defatting and drying of the skin which may result in a burning sensation and a dried, cracked appearance.
Eye Contact: May cause redness, tearing, and irritation of the eyes. Direct contact may cause permanent eye damage.
Inhalation: May cause headache, nausea, dizziness, and loss of coordination. Continued inhalation may result in unconsciousness and death.
Ingestion: May be harmful if swallowed. Aspiration of the material into the lungs can cause chemical pneumonitis, which can be fatal.
Carcinogen: Contains trace amounts of Naphthalene (0.0-0.6% w/w) and bis(2-Ethylhexyl) phthalate (0.2 – 0.4% w/w), which are IARC category 2B possible carcinogen
Aggravation of Pre-existing Conditions: Persons with pre-existing skin, eye, or lung disorders may be more susceptible to the effects of the substance.

12. ECOLOGICAL DATA

Acute Toxicity to Fish: LC50 (96 hr) 8.5 mg/L (Calculated)

Acute Toxicity to Aquatic Invertebrates: EC50 (48 hr) 4.3 mg/L (Calculated)

Toxicity to Aquatic Plants: EC50 algae 4.1 mg/L (Calculated)

Toxicity to Microorganisms: High concentrations may be harmful to sewage treatment plant microbes.

Chronic Toxicity to Fish: No data available

Chronic Toxicity to Aquatic Invertebrates: No data available

Persistence and Degradability: Expected to degrade readily and rapidly in the presence of oxygen

Bioaccumulation Potential: This material is not expected to bioaccumulate.

Mobility in the Soil: Expected to move slowly in soil and water.

Other Adverse Effects: No data available.

13. DISPOSAL INFORMATION

Waste Disposal Method: Liquid material is an ignitable waste (D001). Dispose of material in accordance with all Federal, State, and Local regulations.

14. TRANSPORT INFORMATION

Domestic USDOT: Non-Regulated Material in containers <119 gallons

IMO/IATA:

Proper Shipping Name: PAINT

Hazard Class: 3

UN: UN1263

Packing Group: PGIII

Marine Pollutant: No

15. REGULATORY INFORMATION

SARA 311/312: Yes. (Fire, Acute, Chronic).

OSHA: This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200).

TSCA: Components of this material are listed or are exempt from the EPA TSCA Inventory of Chemical Substances.

California Proposition 65: WARNING! This product contains a chemical known to the State of California to cause cancer.

91-20-3 Naphthalene

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

117-81-7 bis(2-Ethylhexyl) phthalate

91-20-3 Naphthalene

Massachusetts Right To Know:	91-20-3	Naphthalene	0.0 – 0.6
	95-63-6	1,2,4-Trimethylbenzene	0.0 – 0.6
	108-67-8	1,3,5-Trimethylbenzene	0.0 – 0.1
	1330-20-7	Mixed xylene isomers	0.0 – 0.8
	108-88-3	Toluene	0.0 – 0.2

Pennsylvania Right To Know:	Proprietary	Solvent Naphtha	10.0 – 11.1
	98-56-6	p-Chlorobenzotrifluoride	50.0 – 60.0
	91-20-3	Naphthalene	0.0 – 0.6
	95-63-6	1,2,4-Trimethylbenzene	0.0 – 0.6
	108-67-8	1,3,5-Trimethylbenzene	0.0 – 0.1
	1330-20-7	Mixed xylene isomers	0.0 – 0.8
	108-88-3	Toluene	0.0 – 0.2

New Jersey Right To Know:	Proprietary	Solvent Naphtha	10.0 – 11.1
	98-56-6	p-Chlorobenzotrifluoride	50.0 – 60.0
	91-20-3	Naphthalene	0.0 – 0.6
	95-63-6	1,2,4-Trimethylbenzene	0.0 – 0.6
	108-67-8	1,3,5-Trimethylbenzene	0.0 – 0.1
	1330-20-7	Mixed xylene isomers	0.0 – 0.8
	108-88-3	Toluene	0.0 – 0.2

Section 16 Additional Information

The regulatory information provided is not intended to be comprehensive. Other Federal, State and Local regulations may apply to this material.

DISCLAIMER: Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, manufacturer makes no representations as to the completeness or accuracy thereof.