1. Identification of the substance and manufacturer

Trade Name: PRECAUTION BLUE

Product Code: 0000200653

Manufacturer/Supplier: Seymour of Sycamore 917 Crosby Avenue

& SEAMORE,

Sycamore, IL 60178 USA

Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEM-TEL 1-800-255-3924, 813-248-0585 * if located outside of the U.S.*

2. Hazard(s) identification:

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms









Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smo

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international

egulations.

3. Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
64742-89-8	VM&P Naphtha	17.49%
74-98-6	propane	17.01%
1317-65-3	Calcium Carbonate	14.97%
106-97-8	n-butane	9.99%
64742-47-8	Mineral Spirits	4.53%

4. First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints

After Skin Contact: Remove contaminated clothing. Wash exposed area with soap and water.

After Eye Contact: Rinse opened eye for several minutes under running water. Then consult a doctor

After Swallowing:

Rinse out mouth and then drink plenty of water
Rinse mouth with water. Do not induce vomiting

Most Important Symptoms and Effects:

Indication of any immediate Medical

Dizziness

Attention Needed: No further relevant information available

5. Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for

firefighters: A respiratory protective device may be necessary.

Safety Data Sheet

Trade name: GREEN FLUORESCENT

6. Accidental release measures Personal precautions, protective equipment and emergency

procedures: Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol

Methods and material for

containment and cleaning up: Ensure adequate ventilation

7. Handling and storage:

Precautions for safe handling Use only in well ventilated areas

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in sub

freezing conditions. Store locked up.

8. Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:			
74-98-6 propane			
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm		
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm		
TLV (USA)	refer to Appendix F inTLVs&BEIs book; D,		
106-97-8 n-butane			
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm		
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm (EX)		

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Wash hands after use.

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases **Breathing equipment:**

where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you

suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9. Physical and chemical properties

Appearance: Aerosol Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. Boiling point: -44 °C (-47.2 °F) -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Extremely flammable **Decomposition temperature:** Not determined

Auto igniting: Product is not self-igniting

Danger of explosion: In use, may form flammable/explosive vapour-air mixture

Lower Explosion Limit: 1.7 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor pressure: Not determined

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density: Not determined Evaporation rate: Not applicable

Partition coefficient: n-octonal/water: Not determined

Solubility: Not determined Viscosity: Not determined Water: 24.4 %

10. Stability and reactivity

Reactivity: Stable at normal temperatures

Conditions to avoid: Do not allow to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures

Chemical Stability: Not fully evaluated

Possibility of hazardous reactions: No dangerous reactions known

Incompatible materials: No further relevant information available No dangerous decomposition products known Hazardous decomposition:

Printing date 01/04/2018 acc. to OSHA HCS Revised On 01/02/2018

Safety Data Sheet

Trade name: PRECAUTION BLUE

11. Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

LC50/4 h 658 mg/l (rat) Inhalative

Information on toxicological effects: No data available Skin effects: No irritant effect Eye effects: No irritating effect

Sensitization: No sensitizing effects known

12. Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes

Bioaccumulative potential: No further relevant information available Mobility in soil: No further relevant information available Other adverse effects: No further relevant information available

13. Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must

be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14. Transport Information

UN-Number UN1950 DOT N/A UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable

1950 Aerosols **ADR**

Transport hazard class(es):

2.1 Class Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group:

UN "Model Regulation": UN1950, Aerosols, 2.1

15. Regulatory Information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

Toxic Substances Control Act

(TSCA): All hazardous ingredients for this product are found on the inventory list of substances.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

WHMIS Symbols for Canada: A - Compressed gas **EPA:** None of the ingredients listed

16. Other Information

Contact: Regulatory Affairs Date of preparation / last revision 01/04/2018 / -