



## BonTique™

### Antique Agent

BonTique™ Antique Agent is a product that enables to create the look of using an antique powder release AFTER you complete your stamp job. It will allow you to easily create a multi-toned, yet natural finish on almost any new or existing textured concrete surface. BonTique™ is a portland cement based product designed to be mixed in water and applied as a spray on wash and will provide both good color penetration and adhesion. The antique wash will run from the high spots and settle in the low spots providing real contrast to the surface. Once sealed, the surface will provide a natural mottled look for years to come.

#### FEATURES & BENEFITS

- Create an antique finish on stamped concrete surfaces.
- Restore or create color on old/faded textured surfaces.
- Long lasting when sealed and proper upkeep maintained.
- UV stable pigments resist fade.
- Can use multiple colors to create more effects.
- Avoid the mess of using messy powder release.
- Small amount provides great coverage.

#### TYPICAL APPLICATIONS

BonTique™ is ideal for use on any newly textured concrete surface where a contrasting color is desired for a more decorative look but traditional release agent may not an option. This product can be used after traditional use with a powder release agent to provide multiple contrasting colors to a decorative surface. BonTique™ is also an excellent product to use in rejuvenating existing textured surfaces that have suffered long term fade from sun and weather.

#### COVERAGE

Application Surface	Prepared Gallon	Second Coat (option)
Prepped concrete	225 - 300 sq ft	225 - 300 sq ft

*Typical 6 oz per gallon applications will yield approximately 8 gallons of BonTique™ wash. That approximates 1800 sq ft of coverage per container on the low end. Lesser concentrations such as 2 and 4 ounce per gallon will provide increased coverage..*

#### DIRECTIONS FOR USE

Thoroughly clean the concrete surface before applying BonTique™. Any existing sealer must be removed if using on older concrete surfaces. The surface should be free from all sealers, dirt, oil, paint, moss, dust, and other contaminants. This includes cleaning off of any latent liquid release that may have been used for the the stamping process. Though etching is usually not necessary bear in mind that the preferred surface is similar to that getting a normal concrete sealer. We recommend dampening the surface before you apply the BonTique™ especially in hotter weather since the hot concrete surface will absorb and dry the material quickly. Pour one gallon of clean water into a 5-gallon pail, add 3 scoops (**6 ounces**) of BonTique™ powder to the water and mix briskly, making sure all powder is dissolved in the bucket. Add mix to a pump sprayer that has a large Tip opening and apply evenly over the entire surface. If you do not have a sprayer with an adequate tip you may also use something as simple as a garden watering can. You will need to continuously shake the sprayer to minimize settling of the mixture. Try and avoid puddling material heavy in any one spot. A large push broom is often used to help move the product uniformly over the surface. If no broom is available and heavy puddles occur, can remove the excess with a wet sponge. Once complete allow the BonTique™ wash to dry for 12-24 hours. Brushing with a broom the next day can also be used to remove more material from high spots thereby increasing the contrast of the surface. The BonTique™ powder may be increased or decreased depending on the amount of color wanted. For lighter effects simply use only 1 or 2 scoops instead of 3. For more intensity you can increase the amount per batch though be aware that higher loads will become increasingly difficult to keep in suspension.

**SEALING** The longevity of BonTique™ will rely on the surface being maintained with a quality decorative sealer to lock in the color and provide protection from the sun and other elements.

#### CLEAN UP & REMOVAL

Sprayers, applicators and associated tools should be thoroughly cleaned with soap and water **before** the BonTique™ dries. Once dry you may use cleaners associated with the cleaning of latent concrete.

#### PRECAUTIONS & LIMITATIONS

Surface profile can significantly determine the strength and intensity of color.

\*If applying over an existing textured surface, proper adhesion and compatibility tests are essential. When using this product, the substrate preparation, application, performance and all other liabilities are strictly the end users responsibility. Bon Tool Co. and it's affiliates offer no guaranty, warranty or other claims to the success or results from the use of this product. Bon Tool Co. warrants the product to be free of defects and will replace or refund the purchase price of the product in the case that said products are proven defective. Any consequential damages including any labor costs are not covered by this warranty and are therefore not recoverable from the manufacturer or associated reseller.